



US009638297B2

(12) **United States Patent**
Son et al.

(10) **Patent No.:** **US 9,638,297 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **RACK BAR SUPPORTING DEVICE FOR STEERING GEAR**

(71) Applicant: **ERAE AUTOMOTIVE SYSTEMS CO., LTD.**, Daegu (KR)

(72) Inventors: **Chang-Wook Son**, Daegu (KR);
Seong-Hun Bae, Daegu (KR);
Min-Young Choi, Daegu (KR);
Jin-Woong Lee, Daegu (KR); **Je-Won Kim**, Daegu (KR)

(73) Assignee: **ERAE AUTOMOTIVE SYSTEMS CO., LTD.**, Daegu (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 77 days.

(21) Appl. No.: **14/384,841**

(22) PCT Filed: **Mar. 4, 2013**

(86) PCT No.: **PCT/KR2013/001696**

§ 371 (c)(1),

(2) Date: **Sep. 12, 2014**

(87) PCT Pub. No.: **WO2013/137576**

PCT Pub. Date: **Sep. 19, 2013**

(65) **Prior Publication Data**

US 2015/0020619 A1 Jan. 22, 2015

(30) **Foreign Application Priority Data**

Mar. 14, 2012 (KR) 10-2012-0025993

(51) **Int. Cl.**

F16H 19/04 (2006.01)

B62D 3/12 (2006.01)

F16H 55/28 (2006.01)

(52) **U.S. Cl.**

CPC **F16H 19/04** (2013.01); **B62D 3/123** (2013.01); **B62D 3/126** (2013.01); **F16H 55/283** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC .. **F16H 19/04**; **F16H 2055/281**; **F16H 55/283**; **B62D 3/123**; **B62D 3/126**

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,095,482 A * 6/1978 Kirschner B62D 3/123

74/422

4,788,878 A * 12/1988 Morita B62D 3/123

74/409

(Continued)

FOREIGN PATENT DOCUMENTS

DE 102009028380 * 2/2011 B62D 3/123

DE WO 2011101196 A1 * 8/2011 B62D 3/123

(Continued)

Primary Examiner — William Kelleher

Assistant Examiner — Randell J Krug

(74) *Attorney, Agent, or Firm* — Novick, Kim & Lee, PLLC; Jae Youn Kim

(57) **ABSTRACT**

A rack bar supporting device is a device for supporting a rack bar of a steering apparatus of a vehicle toward a pinion shaft and includes a rack bearing and a biasing assembly. The biasing assembly includes an adjustment plug, an adjustment assembly and a support plate assembly. The adjustment assembly includes an adjustment member and a first biasing member. The support plate assembly includes a first support plate, a second support plate, a second biasing member which provides a force for pushing the first support plate along the biasing axis against the second support plate, and a connection structure which connects the first and the

(Continued)

